

Aaton power NiMH & Cha-3

- compact, sturdy, recellable NiMh batteries
- silent and safe charger for long lasting battery cells



One **CAM-NiMH** camera battery pack runs thirty XTR and twenty five Aaton 35-III 400 foot magazines. A set of two **CANT-NiMH** Cantar battery packs ensure ten to fifteen hours of audio recording on set.

On the **CAM-NiMH** flavor (see pic.), a fuse protected Lemo-6 socket is provided for accessories demanding more than 500 mA; this prevents large cur-

rents to flow through the camera electronic housing.

On the **CANT-NiMH** flavor, a metallic post holds the battery flush to the Cantar steel carrier and ensures the grounding of the metal case against EMC.


Technical Specifications:
12.5V, 3.8 to 4Ah;
recellable case (4 CHc 2.5x4 screws); thermal sensor on pin 3 shuts down the Cha-N chargers if cells reach 60°C.

Size: 145 x 73 x 36mm.
Weight: 720g.

The Cha-3 charger simultaneously charges two 12.5V batteries under microprocessor control. Very safe 3.5 hour charging time, temperature and ΔV sensing plus a six hour auto switch-off. Battery charge monitoring by LEDs:

Charging 
Charged 
Error 

Technical Specifications:
Totally silent.
Automatic 110/220V.
Spare fuse inside the AC socket (5x20mm, 2A).
Size: 182x88x57mm
Weight: 630gr.



Lemo-6 socket outside, counterclockwise:
1 - Batt
4 + Batt
2, 3, 5 & 6 NC

XLR4 socket outside, counterclockwise:
1 - Batt
3 Thermal sensor
4 + Batt

