FGG.0B.302.CLAD52Z

SUMMARY

Image is illustrative, deviations may

IP Where

Low	1
High	0
Dust	0
Drop	0
Spray	0
Water	0
Powder	0

Download

- Request a quote
- Catalog
- Set cable assembly instructions

Series	0B
Termination type	wire crimp
IP rating	00
Cable Ø	4.00 – 5.00 mm
Status	active
Alternative part	
Matching parts	FGG.0B.302.Xxx FHG.0B.302.Xxx.PG13

TECHNICAL DETAILS

Mechanics

Short Style/Model	FG = Straight plug, cable outlet and nut for fitting a barrel relief
Keying	1 key (Male=S, plug male contacts, receptacle female contacts)
Housing Material	Brass (a recent phenolic shell and socket nut, nickel plated brass latch sleeve and polyacetal
Variant	Z = Nut for fitting a barrel relief
Weight	6.40 g

Performance

Configuration	0B.302 : 2 core voltage
Insulator	LCP FR30 (UL 94 / V-0/1.2, depends on material thickness)
Rated Current	10 Amps

Specifications

Contact: Type: Socket
Contact: Dia.: 0.9 mm (0.035in)
Socket: Dia.: 1.0 mm (0.039in)

LEMO products and services are provided "as-is". LEMO makes no representations with regard to LEMO products or services in view of their specific intended purpose, including or excluding compatibility, or suitability. The user is fully responsible for the product and applications using LEMO components.